



The Strike Flat Panel Video Visitation Correctional Enclosure is designed to be used in a correctional environment for either inmates or visitors as a secured enclosure for housing Video Visitation equipment and preventing unauthorized access or use. The internal electronics are custom configured to meet the owner's needs while utilizing a flat panel LCD NTSC monitor.

The Strike Flat Panel Video Visitation Correctional Enclosure eliminates the costs and safety concerns associated with unauthorized access or abuse of the audio and video equipment used for Video Visitation conferences. Inmate Video Visitation stations distributed throughout a facility also eliminate the need to transport prisoners and visitors, whether to/from a general housing unit, or a medical or segregation unit, for the purpose of a visit.



This unit is specifically built for the environment in which it is meant to reside. The unit is constructed of 14-gauge steel to withstand any physical abuse. This equipment enclosure will far surpass typical particle board enclosures on the market that are prone to decay and deterioration due to hard daily use or from being in environments with high humidity. The Strike Video Visitation Correctional Enclosure is intended to be mounted directly to a hard surface wall, covering appropriately located electrical and system wiring outlets. Mounting holes accommodate up to 1/2" diameter mounting hardware

A large polycarbonate window in the front of the unit provides full screen viewing while also providing protection for the equipment. The 3/8" polycarbonate window absorbs the hardest of blows without breaking. The polycarbonate window is affixed to the enclosure housing with a space-age 3M tape that is used to mount metal siding on tractor trailers and commercial buses without the use of rivets. In addition to the tape, the window is further secured with internally bolted z-brackets. This unit will not be broken into easily!

Access into the interior of the unit is through the front panel that is secured with tamper proof security screws.

The unit is configurable to provide either single or dual armored cord handset use. Optionally, hands-free access units are available to meet ADA requirements. These options are possible with the use of proper internal electronic equipment.

The Strike Flat Panel Video Visitation Correctional Enclosure is heavy-duty powder coated for durability of finish. It can be custom colored to match any institution's existing color scheme. Standard color is dark gray. Additional colors and color matching available (may incur additional cost). Stainless Steel available as an option.

Form meets functionality in the Strike Video Visitation Correctional Enclosure. The attention to detail and rugged construction means that you don't have to worry about the unit, or the equipment it protects, being destroyed in normal use. Welded panels and heavy-duty construction create a unit that can be used for years to come.



Video Visitation equipment shown is not included with enclosure. Actual unit will vary from unit shown due to recent engineering changes.

Enclosure Specifications (without handsets):

Exterior: 22"W x 8"D x 23"H (top slopes to 20.5"H in front)

Weight: 45 lbs. Approx.

Front Opening:

Fitted with a 3/8" thick piece of unbreakable polycarbonate. The window opening is 15"W x 13 5/8"H with an area designed for the placement of a camera.

Installation Specifications: Wall-mount at 34" from enclosure bottom to floor when using 16" seats or stools. Electrical & network cabling: single gang boxes in wall to be mounted 6-8" apart at 48-51" from tops of boxes to the floor; external surface mount wiring conduit to enter from left side of enclosure at approximate center lines of 48.75" and 50.75" above the floor when mounted at the 34" recommended height.

Note: When ordering, selection of either inmate or visitor enclosure must be indicated, as well as single or dual handset model, color or stainless option, and external or internal wiring specified.